



No.	item	material	数量	备注
42	down baffle	zinc-coated steel plate t=0.8	1	
41	insulation board	mica plate t=1.5	4	
40	flth supporter	zinc-coated steel plate t=0.8	1	
39	PTC element	900W/240V	1	
38	bearing bushing	rubber	1	
37	Sleeve bearing	copper $\phi 3 \times \phi 11 \times 8\text{mm}$	1	
36	up baffle	zinc-coated steel plate t=0.8	1	
35	fluer	ceramic	1	
34	turbo fan	varnium $\phi 60.5 \times 185\text{mm}$ blades	1	
33	back baffle	zinc-coated steel plate t=0.8	1	
32	right bracket	zinc-coated steel plate t=0.8	1	
31	bracket of motor	zinc-coated steel plate t=1	1	
30	motor	240V 1900r/min	1	
29	the down right bracket	zinc-coated steel plate t=1	1	
28	cable box	PP	1	
27	the cover of wire hot	PP	1	
26	power cord	PVC 36 x 1-1.5mm ²	1	
25	knob of thermostat	ABS	1	
24	adjustable thermostat	STC-50 120C 12A/250V	1	
23	knob of switch	ABS	1	
22	select switch	FZ31-9 15A/250V	1	
21	right shell	PP	1	
20	fill sets	Silicon	1	
19	ceramic	ceramic	4	
18	heating element	750W/240V	2	
17	quartz tube	quartz $\phi 12 \times 442$	2	
16	reflector	stainless steel t=0.25	1	
15	right bracket	zinc-coated steel plate t=0.5	1	
14	the up right bracket	zinc-coated steel plate t=0.5	1	
13	pilot lamp	upon bulb 220V-240V	1	
12	safety switch	FD-2 15A/250V	1	
11	body shell	cold plate t=0.5	1	
10	the up left bracket	zinc-coated steel plate t=0.5	1	
9	up bracket	zinc-coated steel plate t=0.5	1	
8	fuse	FD152S 152C	1	
7	fuse clip	zinc-coated steel plate t=1	1	
6	stiffener-bar	zinc-coated steel plate t=1.5	4	
5	left shell	PP	1	
4	left bracket	zinc-coated steel plate t=0.5	1	
3	the down left bracket	zinc-coated steel plate t=0.5	1	
2	bruckle	stainless steel t=0.25	2	
1	shield	galumie $\phi 2 \phi 3$	1	

YIXIONG ELECTRICAL APPLANCE CO., LTD		NGF-24DP	
EXPLODED VIEW		EXPLODED VIEW	
标记	处数	分区	更改文件号
设计			标准化
审核			批准
工艺			
阶段标记		重量	比例
共 张		第 张	
NGF24DP-6-01			

底图/用底图
旧底图号
底图号
签字
日期